TECHNICAL **SPECIFICATIONS**

PIXMA G2560

GENERAL SPECIFICATIONS

Functions

PRINTER SPECIFICATIONS

Print Resolution Print Technology

Mono Print Speed Colour Print Speed

Photo Print Speed **Borderless Printing**

Two Sided Printing

CARTRIDGES AND YIELDS

Standard Ink Cartridges

Cartridge Yield (Plain paper)

Cartridge Yield (Photo print)

PAPER SUPPORT

Paper Types

Maximum Paper Input

Paper Sizes

Paper Weight

SCANNER SPECIFICATIONS Scanner Type Scanner Resolution (Optical)

Line Scanning Speed

Scanning Depth (Input / Output) Maximum Document Size

COPIER SPECIFICATIONS

Copy Speed

Multiple Copy

High Speed Print, Scan & Copy

Up to 4800 x 1200 dpi [1]

2 FINE Print Head (Black and Colour)

Refillable ink tank printer approx. 10.8 ipm [2] approx. 6.0 ipm [2]

Borderless 10x15cm: Approx. 45 seconds [3]

A4, LTR, 4" x 6", 5" x 7", 7" x 10", 8" x 10",

Square (89 mm x 89 mm), Square (127 mm x 127 mm), Card Size (91 mm x 55 mm) [4]

Manual operation

GI-51 <PGBK> GI-51 <C> GI-51 <M>

GI-51 <Y>

A4 colour documents printing ^[5]
Black: 6,000 pages (Economy mode 7,600 pages) ^[6]

Colour: 7,700 pages * Estimated supplemental vield 10x15cm colour photo printing [7]

Colour: 2,200 photos

* Estimated supplemental vield

Plain Paper

Photo Paper Pro Luster (LU-101). Photo Paper Plus Glossy II (PP-201) Matte Photo Paper (MP-101),

Glossy Photo Paper "Everyday Use" (GP-501) High Resolution Paper (HR-101N),

Envelope, Photo Paper Plus Semi-gloss (SG-201),

Cardstock
Restickable Photo Paper(RP-101) Magnetic Photo Paper(MG-101)
Dark Fabric Iron on Transfers (DF-101), Light Fabric Iron on Transfers (LF-101), Double sided Matte Paper (MP-101D)

Rear Tray: Max. 100 sheets (plain paper)

A4, A5, A6, B5, LTR, LGL, Executive (184.2 mm x 266.7 mm),

Executive (184.2 mm x 266.7 mm), Legal (215 mm x 345 mm), 4" x 6", 5" x 7", 7" x 10", 8" x 10", Envelopes DL, Envelopes COM10, Envelopes C5, Square (89 mm x 89 mm), Square (127 mm x 127 mm),

Card Size (91 mm x 55 mm)

[Custom size] width 55 mm - 216 mm, length 89 mm - 1200 mm

Rear Tray: Plain paper: 64 - 105 g/m²
Canon specialty paper: max paper weight: approx. 275 g/m²
(Photo Paper Plus Glossy II PP-201)

CIS flatbed photo and document scanner 600 x 1200 dpi ^[8]

Colour: 3.5 ms/line(300dpi) Greyscale: 1.5 ms/line(300dpi)^[9] Colour: RGB each 16bit / 8bit Grevscale: 16 bit / 8 bit

A4/ITR

sFCOT: Approx. 23 sec [10] sESAT: Approx. 3.2 ipm 99 copies (max.)

Copy Functions

Copy Zoom

Document Copying, Photo Copying, Borderless copy, 2-on-1 and 4-on-1 copy,

Frame erase copy, ID copy 25 - 400% (in 1% increments)

Full Dot I CD

Fit to page
A5 to A4, B5 to A4, A4 to A5 and A4 to B5

GENERAL Display

OS Compatibility

Display Languages

32 Languages Selectable: Japanese, English(mm & inch), German, French, Italian, Spanish, Dutch, Portuguese, Norwegian, Swedish, Danish, Finnish, Russian, Czech, Hungarian, Polish, Slovene, Turkish, Greek, Simplified Chinese, Traditional Chinese, Korean, Indonesian, Slovakian, Estonian,

Latvian, Lithuanian, Ukrainian, Romanian, Bulgarian, Croatian, Vietnamese

Standard Interface Hi-Speed USB (USB B Port) Easy-PhotoPrint Editor Software [11] **Printer Features**

Windows 10, Windows 8.1, Windows 7 SP1 Operation can only be guaranteed on a PC with

pre-installed Windows 7or later.
Printer driver, IJ Printer Assistant Tool and IJ Network Device Setup Utility are available with following OS. Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Chrome OS

Mac: OS X 10.12.6 \sim macOS 10.15 $^{[12]}$

Minimum System Windows: 2.0GB or more Mac: 1.0GB or more Requirements

Note: for bundled software installation. The necessary amount of hard disk space required.

Display: 1024 x 768 XGA

Printer Driver

IJ Printer Assistant Tool

Approx. 445 x 330 x 167

approx. 51.0dB(A) [13]

Easy-PhotoPrint Editor (download)

PHYSICAL FEATURES

Software Included

Weight Dimensions (W x D x H) **Acoustic Noise Levels**

Operatina Temperature

Operating Humidity 10-90%RH (no dew condensation)

Power Source AC 100-240V, 50/60Hz

Off: Approx. 0.2W Power Consumption

Standby (USB connection to PC): Approx. 0.6W Standby (all ports connected): Approx. 0.6W Time to enter Standby mode: 11 minutes 4sec Copying: Approx. 15W [14]

0.1 kWh [15

approx. 6.4 kg

5-35°C

Typical Electricity Consumption

Ulnk droplets can be placed with a minimum pitch of 1/4800 inch

[2] A4 document print speed on plain paper is measured based on average of ESAT in Office Category Test of ISO/IEC 24734 standard.

[3] Photo print speed is based on default driver setting using ISO/JIS-SCID N2 standard on Canon Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

14) Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers

[5] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart and continuous printing simulation with the replacemen after initial setup.

[4] The economy mode reduces the black ink consumption by lowering the density, 26% more pages than the standard mode can be printed

[7] Page Yield is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement after initial setup.

(B) Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

191 The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.



TECHNICAL SPECIFICATIONS

PIXMA G2560

Footnote:

- 110 Colour document copy speed is measured based on average of sFCOT and sESAT in Performance Test of ISO/IEC 29183 standard. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- [11] The Easy-PhotoPrint Editor software requires an Internet connection and is compatible with the following operating systems; Microsoft Windows 10 (64-bit/32-bit), Microsoft Windows 8.1 (64-bit/32-bit), Microsoft Windows 7 SP1 (64-bit/32-bit), macOS High Sierra v10.13, macOS Sierra v10.12, Mac OS X EI Capitan v10.11 and Mac OS X EI Capitan v10.10.5. Minimum Windows and macOS/Mac OS X requirements are: 2GB of RAM and a monitor with 1024x768 resolution.
- [12] Some functions may not be available with these Operating Systems. Please refer to the manual or website for details.
- [13] Plain Paper(A4, B/W). Acoustic Noise is measured based on ISO7779 standard.
- [14] Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- poper using eartern scrings.

 Its Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

Standard disclaimers

- All specifications subject to change without notice.
- Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canoneurope.com/ink/yield
- All brand and product names are trademarks of their respective companies.
- Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2020

